



RESOURCE AND PATIENT MANAGEMENT SYSTEM

Practice Management Application Suite

(BPRM)

Installation Guide and Release Notes

Version 3.0 patch 6
March 2018

Office of Information Technology
Division of Information Technology

Table of Contents

1.0	Release Notes	1
2.0	Installation Notes.....	2
2.1	Contents of Distribution	2
2.2	Required Resources.....	2
2.2.1	Standalone Application Server Resources	2
2.2.2	Database Server Resources	2
2.2.3	Workstation Resources	3
2.3	Before You Begin: Installation Issues	3
2.4	Prerequisites.....	3
2.4.1	Ensemble Prerequisites.....	3
2.4.2	BPRM Prerequisites	3
3.0	Installation Overview.....	5
3.1	BMW Database Deployment Strategy	5
4.0	Installing BPRM Patch Update (Existing Sites).....	6
4.1	Uninstall the BPRM Application	6
4.2	Uninstall the MongoDB Application.....	6
4.3	Update HTTP Compression.....	7
4.4	Update Application Pool Identity	8
4.5	Install the BPRM Application	10
4.6	Importing a New BMW CACHE.DAT File	15
4.7	Importing a New BPRM XML File	15
4.7.1	Disable Read Only.....	15
4.7.2	Import the BPRM XML File	16
4.8	Purge the Previous SQL Queries	20
4.9	Start the BPRM Website on the Application Server	20
5.0	Installation Instructions: First-Time Install	21
5.1	Acquire the SSL Certificate.....	21
5.1.1	SSL Certificate Acquisition – IHS Domain	21
5.1.2	SSL Certificate Acquisition – Non-IHS Domain	25
6.0	BPRM Application Server Installation and Configuration.....	26
6.1	Microsoft .NET Framework Verification	26
6.2	Microsoft .NET Framework 4.5 Installation	26
6.3	Internet Information Services 7.0 Installation	29
6.4	Windows Communication Foundation Activation	34
6.5	Adding MIME Types	37
6.6	HTTP Compression Configuration	40
6.7	Moonwalk Web Site Setup.....	42
6.7.1	Add the Application Pool	42
6.7.2	Create a Moonwalk Folder	44

6.7.3	Add the New Site.....	44
6.8	Install the SSL Certificate	45
6.9	Configure the SSL Certificate	47
7.0	BPRM Database Server Installation and Configuration	49
7.1	Assumptions	49
7.2	Importing a New BPRM XML File	49
7.2.1	Disable Read Only.....	49
7.2.2	Import the BPRM XML File	50
7.3	Cache User Creation	54
7.3.1	Create the Moonwalk User	54
7.3.2	Assign User Roles	55
7.3.3	Verify XML Import and Installation.....	57
8.0	Application Deployment to the Web Server	59
8.1	Deploy the BPRM Application.....	59
8.2	Adding a Database after the Installation	64
8.3	Menu and Security Keys.....	68
8.4	Open the BPRM Application	70
Appendix A:	Run the Application Installer from the Command Prompt.....	72
Appendix B:	Running Multiple Instances of BPRM	73
Appendix C:	Application Server Specification Example.....	74
Appendix D:	Disable Logging in IIS Manager	76
Appendix E:	Run Multiple BPRM Web Applications on a Single Server	79
Acronym List	81
Contact Information	82

Preface

This manual describes the installation of the Practice Management Application Suite (namespace BPRM) and any additional support software needed.

BPRM is a browser-enabled graphical user interface for the Indian Health Service (IHS) Resource and Patient Management System (RPMS) applications. It provides improved access to existing RPMS data and streamlines the input of new patient data. In some aspects of its operation and configuration, this suite is also referred to by its development name, *Moonwalk*. It should also be noted that prior to V3.0, the previous namespace for the Practice Management Application Suite was BMW. The BMW namespace now refers only to the CACHE.DAT file used by BPRM and other IHS applications.

The BPRM application suite consumes Cache classes, generated by Fm2Class utility, which maps onto FileMan files. Create, read, update, and delete (CRUD) operations can then be performed over the generated Cache classes (SQL tables) via the ADO.NET provider for Intersystems Ensemble/Cache.

1.0 Release Notes

This patch enables data entry and display of the new Medicare Beneficiary Identifier (MBI) on the Medicare and Rail Road Insurance pages in the Registration module and displays the information on the Face Sheet and Alternate Resource Summary page in the Registration module.

The following describes the changes made in BPRM V3.0 patch 6:

- CR09198 Add MBI field for Medicare billing

2.0 Installation Notes

Prefix: BPRM

Current Version: 3.0 patch 6

2.1 Contents of Distribution

File	Description
bprm0300.06.msi	BPRM Application Installer
bprm0300.06.xml	BPRM data description file
bprm0300.06i.pdf	Version 3.0 Patch 6 Installation Guide and Release Notes

2.2 Required Resources

This section lists the computer resources required for each deployment strategy.

Note: With BPRM v3.0, a separate MongoDB server is no longer needed as CQM processes will remain on the application server. Due to this, additional storage space may be required on the application server.

2.2.1 Standalone Application Server Resources

The following resources are required for a standalone application server:

- Microsoft® Windows® 2008 Server x64 bit (or later)
- Microsoft IIS® 7, 7.5, 8, 8.5 and 10
- Microsoft .NET Framework 4.5 (or later)
- Four processor cores running at 2.0 GHz or faster (for site)
- Eight processor cores running at 2.4 GHz or faster (for area office)
- 4 GB RAM running at 1333 MHz (for site)
- 12 GB RAM running at 1333 MHz (for area office)
- 60 GB minimum free disk space (disk drives should be 10K RPM or faster)

See Appendix C for a listing of specifications for a typical BPRM application server.

2.2.2 Database Server Resources

Database servers running the BPRM application require a minimum 5 GB of free disk space.

2.2.3 Workstation Resources

The following resources are recommended for any workstations accessing the BPRM application:

- Dual-core processor running at 1.8 GHz or faster
- 4 GB of RAM
- 20 GB free disk space
- Screen resolution of 1024 x 768 or higher
- Windows 7 (highly recommended) or Windows XP
- Internet Explorer® 9 (highly recommended) or Internet Explorer 10,11
- Microsoft Silverlight® 5.0 plugin for Internet Explorer (required)

The Silverlight plugin can be rolled out on an enterprise basis using Group Policies or another enterprise deployment tool, or it can be installed individually on the workstation. Silverlight is available from Microsoft at this location:

<http://www.microsoft.com/getsilverlight/get-started/install/default.aspx>.

2.3 Before You Begin: Installation Issues

Internet connectivity on the application server is necessary to download the required installation items.

2.4 Prerequisites

2.4.1 Ensemble Prerequisites

- BPRM v3.0 currently supports only Ensemble version 2012.2.x. Be aware the examples in this Installation Manual reflect Ensemble 2012.2.5. If running a different version, some of the screens may differ slightly from those shown here.
- A BMW-specific CACHE.DAT file (Version 2016.2 or later) must be loaded into the Ensemble server BMW namespace. Acquire this file from OIT SQA; it is not delivered as part of the installation package. Refer to the latest *BMW CACHE.DAT Installation Guide* for more information.

2.4.2 BPRM Prerequisites

The following cache.dat file must be installed:

- BMW Version 2016.2

The following KIDS must be installed:

- PIMS v5.3 p1019

- AG v7.1 p13
- AUT v98.1 p27
- XU v8.0
- BJPC v2.0 p10
- AVA v93.2 p23
- AUPN v99.1 p26
- BSDX v3.0
- EHR v1.1 patch 14
- BCQM v1.0 patch 2

3.0 Installation Overview

The BPRM v3.0 patch 6 installation requires three files. The **bprm0300.06.xml** data description file and the **bprm0300.06.msi** application installation file are specific to the BPRM suite. These two files are included in the BPRM distribution package.

Additionally, a **CACHE.DAT** file (contained in a zipped file) specific to the Ensemble version is also necessary. This **CACHE.DAT** file is used by BPRM as well as other Meaningful Use Stage 2-compliant IHS applications and is not included as part of the distribution package. It must be acquired separately from OIT SQA.

Save the **bprm0300.06.xml** data description file and the zipped file containing the **CACHE.DAT** file to a folder that is accessible to your database server. Similarly, save the **bprm0300.06.msi** file to a folder that is accessible to your application server(s).

Refer to Section 4.0 if an earlier version of BPRM is installed at your site. Follow the instructions in Sections 5.0 through 8.0 to install BPRM for the first time at your site.

3.1 BMW Database Deployment Strategy

To minimize changes to the RPMS database, BPRM adopts a strategy where a separate database is mounted or attached on a current Ensemble/Cache server. This mounted database contains already generated Cache classes against FileMan files.

The classes in the BMW database are generated in a specific package called BMW. The BMW package can be mapped onto the RPMS database, thus enabling the RPMS database to consume the mapped classes. The Cache-generated Classes will reside in the BMW database, yet remain available to the RPMS database, thus achieving the goal of minimizing steps for the BMW database setup when it is scaled onto several sites.

4.0 Installing BPRM Patch Update (Existing Sites)

BPRM patches and updates are released on a periodic basis to address reported issues and to add enhancements. Follow the steps in Sections 4.1 through 4.9 to install an incremental patch or update.

4.1 Uninstall the BPRM Application

Follow these steps to uninstall BPRM:

1. Open the **Windows Control Panel** and select the Programs and Features applet.
2. Select the BPRM application as shown in Figure 4-1 and click **Uninstall**. Be aware that in some cases, the previous namespace (BMW) may display instead of BPRM:




Figure 4-1: Uninstalling BPRM

4.2 Uninstall the MongoDB Application

If you are upgrading from BPRM v3.0, then follow these steps to uninstall the MongoDB services:

1. Open the **Windows Control Panel** and select the Programs and Features applet.
2. Select the MongoDB application and click **Uninstall**.
3. Open the **Windows Control Panel** and select the **Administrative Tools**.

- Use the **Services** option and confirm that the MongoDB and CQM_CAT1_EXTRACT services are no longer listed. If so, it may be necessary to manually remove it.

- To manually remove the services, open the Command Prompt in Administrator mode and enter the following commands:

```
sc delete MongoDB
```

```
sc delete CQM_CAT1_EXTRACT
```

- Confirm that the deletion completes successfully. A server restart may be required to complete the service deletion.

4.3 Update HTTP Compression

Starting in BPRM v3.0 Patch 2, the BPRM application will no longer use the cached data folder. To facilitate this change for existing installs, the complete the following changes on the Application server:

To edit the HTTP compression:

- Using **Windows Explorer**, browse to **C:\Windows\System32\inetsrv\config** as shown in Figure 4-2.

Note: This folder is typically hidden; it may be necessary to manually type the folder path in the Windows Explorer address bar.




Figure 4-2: Location of **applicationHost.config** file

- Open the **applicationHost.config** file with a text editor such as Notepad and find or search for the **httpCompression** tag.

Note: The statements following the tag in the file on the system might not match those in this example.

- Add the following line to the dynamicTypes section:

```
<add mimeType="application/json" enabled="true" />
```

- Once added, the httpCompression section should look similar to Figure 4-3.

```
<httpCompression directory=
  "%SystemDrive%\inetpub\temp\IIS Temporary Compressed Files">
  <scheme name="gzip" dll="%Windir%\system32\inetsrv\gzip.dll"
  dynamicCompressionLevel="5" />
  <dynamicTypes>
    <add mimeType="text/*" enabled="true" />
    <add mimeType="message/*" enabled="true" />
    <add mimeType="application/x-javascript" enabled="true" />
    <add mimeType="application/javascript" enabled="true" />
    <add mimeType="application/json" enabled="true" />
    <add mimeType="*/*" enabled="false" />
  </dynamicTypes>
  <staticTypes>
    <add mimeType="text/*" enabled="true" />
    <add mimeType="message/*" enabled="true" />
    <add mimeType="application/javascript" enabled="true" />
    <add mimeType="*/*" enabled="false" />
  </staticTypes>
</httpCompression>
```

Figure 4-3: Typical applicationHost.config file after changes

- When finished editing the applicationHost.config file, save it and exit from the text editor.

4.4 Update Application Pool Identity

To add the Application Pool:

- Go to the **IIS Manager** and browse to **Application Pools** in the tree structure below your IIS node as shown in Figure 4-4.




Figure 4-4: IIS Manager browsed to Application Pools

- Right-click the **Moonwalk** application pool and select **Advanced Settings**. A dialog similar Figure 4-5 to displays:




Figure 4-5: Application Pool Advanced Settings

- Change the **Identity** value to **LocalSystem**.
- Click **OK** to save the changes and close the dialog.

4.5 Install the BPRM Application

To deploy the BPRM application:

1. Log onto the application server and browse to the location where the BPRM Application Installer file (**bprm0300.06.msi**) is stored.
2. Double-click the **bprm0300.06.msi** file to run the BPRM application installer.

Note: If an error message displays indicating that you do not have sufficient privileges to run the installer, refer to Appendix A for instructions on running the installer from the Administrator command prompt.

3. Once the installer is started, the **BPRM setup wizard** (Figure 4-6) displays.




Figure 4-6: **BPRM Setup Wizard** dialog

4. Click **Next**. The **Select Installation Address** dialog displays.
5. Select **Moonwalk** from the **Site** list.
6. Type the directory name in the **Virtual directory** field, if necessary.
7. Select **Moonwalk** from the **Application Pool** list. Figure 4-7 shows the results:




Figure 4-7: **Select Installation Location** dialog after selection

8. Click **Next**. The **Confirm Installation** (Figure 4-8) dialog displays.




Figure 4-8: **Confirm Installation** dialog

9. Click **Next**. The **Installing BPRM** dialog (Figure 4-9) displays, showing the installation progress.




Figure 4-9: **Installing BPRM** dialog

10. After a few moments of processing, the **Database Configuration** dialog (Figure 4-10) displays.




Figure 4-10: **Database Configuration** dialog

11. In the **Database Configuration** dialog, click **Load Existing Configuration**. The **Configuration File Selection** dialog (Figure 4-11) displays.




Figure 4-11: **Configuration File Selection** dialog

12. Select **Facilities**, and then click **Open**. The **Database Configuration** dialog displays again, with the existing configuration listed, similar to that shown in Figure 4-12.




Figure 4-12: **Database Configuration** dialog - Existing configurations listed

13. After you have specified all the required information in the **BPRM Release Manager** dialog, click **Continue** to complete the installation.
14. A separate screen will display the CQM installation and conversion process. (Figure 4-13) will display to perform the CQM service install.




Figure 4-13: CQM install pop-up

15. A **Moonwalk Setup Status Page** (Figure 4-14) will display to perform a setup check. The checks listed should display as complete. This page can only display results while the Moonwalk website and application pool are started.




Figure 4-14: Moonwalk Setup Status Page

16. When the installation is complete, click **Next**. The **Installation Complete** dialog (Figure 4-15) displays.




Figure 4-15: **Installation Complete** dialog

17. Click **Close** to exit the dialog.

4.6 Importing a New BMW CACHE.DAT File

Follow the steps outlined in Section 5 of the *BMW CACHE.DAT Installation Guide* to import a new BMW CACHE.DAT file.

4.7 Importing a New BPRM XML File

A BPRM patch or update is contained within a single XML file. Follow the steps in Sections 4.7.1 through 4.7.2 to import a new BPRM XML file.

4.7.1 Disable Read Only

To import the **bprm0300.06.xml** file, set the BMW database to allow write access. If the database is set to **Read Only**:

1. Browse to the **Local Databases** window of the Ensemble Management Portal following this path:

Home > System Administration > Configuration > System Configuration > Local Databases.

2. Click **Edit** in the row corresponding to the **BMW** database.
3. In the window displayed, set the **Read Only?** field to **No**.

Once the patch is installed, re-enable Read Only mode by repeating these steps and setting the **Read Only?** field to **Yes**.

4.7.2 Import the BPRM XML File

To import the **bprm0300.06.xml** file:

1. From the **Ensemble/Cache System Management Portal Home** window, click **System Explorer**, and then click **Classes**.
2. In the **Classes** window (Figure 4-16), select the **BMW** namespace in the **LookIn:** section on the left side of the window.




Figure 4-16: **Classes** window

3. Click **Import**. The **Import Classes** dialog shown in Figure 4-17 displays .




Figure 4-17: **Import Classes** window

4. Click **Browse** and navigate to the **bprm0300.06.xml** file in the folder it is saved as described in Section 3.0. Select the **bprm0300.06.xml** file and click **Next**.
5. Next, a listing (Figure 4-18) will display, showing the contents of the XML file.




Figure 4-18: **Import Classes** window - Content listing

6. Click **Import**. After a few moments of processing, a listing of the imported classes will display. Figure 4-19 shows an example of a typical listing.




Figure 4-19: **Import Classes** window - Import listing

7. Scroll to the bottom of the listing to confirm the **Load finished successfully** message displays (Figure 4-20).




Figure 4-20: **Import Classes** window - Load finished successfully

The importation of the BPRM XML file is now complete.

4.8 Purge the Previous SQL Queries

To purge any previous SQL queries:

1. From the Ensemble/Cache **System Management Portal Home** window, click **System Explorer > SQL > Browse SQL Schemas**.
2. On the left side of the window, select your RPMS database. In the example shown in Figure 4-21, **EBCI** is selected. Your database will likely have a different name.




Figure 4-21: Purge Queries - Ensemble 2012 systems

3. Click **Purge Queries**.

4.9 Start the BPRM Website on the Application Server

If previously stopped, re-start the BPRM (Moonwalk) website.

The installation of the BPRM patch or update is now complete.

Note: Please review the additional steps for disabling the IIS Manager Logging feature in Appendix D.

5.0 Installation Instructions: First-Time Install

BPRM contains components that run on both the RPMS server and the client personal computer. As a result, the installation instructions are separated into these actions:

- Application Server Installation (Section 6.0)
- Database Server Installation (Section 7.0)
- Application Installation (Section 8.0)

The application operates in a web-based environment; there is no separate installation necessary on workstations other than the items listed in Section 2.2.3.

5.1 Acquire the SSL Certificate

BPRM utilizes the Secure Sockets Layer (SSL) protocol to ensure secure communications between its components. If your site is not on a secure domain, you must acquire an SSL certificate. If your site is on a secure domain, an SSL certificate is not necessary and you can skip all of this section (5.1), and Sections 6.8 and 6.9.

Note: Since the SSL certificate acquisition may take up to 24 hours, it is recommended that you acquire the SSL certificate before beginning the BPRM installation.

The process for acquiring this certificate for sites on the IHS domain is different than that used by sites that are not on the IHS domain.

5.1.1 SSL Certificate Acquisition – IHS Domain

If your site is on the IHS domain, use the following steps to acquire your SSL certificate:

1. Click **Start, Administrative Tools, and Internet Information Services (IIS) Manager**.
2. Click the server name. The **IIS Manager** dialog (Figure 5-1) displays.




Figure 5-1: Internet Information Services (IIS) Manager

3. In the center panel, double-click **Server Certificates** in the **Security** section (near the bottom of the panel).





Figure 5-2: Internet Information Services (IIS) manager - Server Certificates

4. In the **Actions** panel (on the right), click **Create Certificate Request**. The **Request Certificate Wizard** (Figure 5-3) displays.
5. In the **Distinguished Name Properties** dialog, enter the information as follows:
 - **Common Name:** The name through which the certificate will be accessed (usually the fully-qualified domain name, e.g., “NPACSMBMW.d1.na.ihs.gov”).
 - **Organization:** The legally registered name of your organization or company.
 - **Organizational unit:** The name of your department within the organization (e.g., IHS).
 - **City/locality:** The city in which your organization is located.
 - **State/province:** The state in which your organization is located.
 - **Country/region:** The two-character country code.



The screenshot shows a dialog box titled "Request Certificate" with a sub-title "Distinguished Name Properties". It contains a text area with instructions: "Specify the required information for the certificate. State/province and City/locality must be specified as official names and they cannot contain abbreviations." Below this are several input fields: "Common name:" with the value "NPACSMBMW.d1.na.ihs.gov", "Organization:" with "HHS", "Organizational unit:" with "IHS", "City/locality" with "Albuquerque", "State/province:" with "NM", and "Country/region:" with a dropdown menu showing "US". At the bottom are buttons for "Previous", "Next", "Finish", and "Cancel".

Figure 5-3: Request Certificate Wizard - Distinguished Name Properties

6. Click **Next**. The **Cryptographic Service Provider Properties** dialog (Figure 5-4) displays.



Figure 5-4: Request Certificate Wizard - Cryptographic Service Provider Properties

7. Leave both settings at their defaults:
 - **Cryptographic service provider:** Microsoft RSA SChannel Cryptographic Provider.
 - **Bit length:** 2048.
8. Click **Next**. The **File Name** dialog (Figure 5-5) displays.




Figure 5-5: **Request Certificate - File Name** dialog

9. Type a path and file name for the certificate request file. Make note of the chosen filename and the save location. You will need to open this file as a text file and copy the entire body of it (including the Begin Certificate Request and End Certificate Request tags) into the online order process when prompted.
10. Click **Finish** to save the SSL certificate request file.
11. E-mail the file to IHSServerCertificateRequest@ihs.gov. Request the SSL Certificate in CER format for the BPRM Application. A certificate will be issued within 24 hours and e-mailed to the originator of the request. Once the certificate is received, proceed with the BPRM installation as described in Sections 6.0 through 8.0.

5.1.2 SSL Certificate Acquisition – Non-IHS Domain

If the site is not on the IHS domain, the steps for acquiring an SSL certificate will vary, depending on the certificate provider. Several vendors (e.g., GoDaddy, Thawte, and Verisign) provide SSL certificates, and the process for acquiring the certificate is different for each.

Follow the steps provided by the SSL certificate vendor to acquire an SSL certificate, and proceed to the BPRM installation instructions in Sections 6.0 through 8.0.

6.0 BPRM Application Server Installation and Configuration

6.1 Microsoft .NET Framework Verification

As mentioned in Section 2.2.1, Microsoft .NET Framework 4.5 is required on the BPRM application server. To determine if it is already installed:

1. From the Windows **Start** menu, select **Control Panel**.
2. Click **Programs and Features**. A listing similar to that shown in Figure 6-1 displays.




Figure 6-1: **Programs and Features** listing

3. Review the listing, looking for any **Microsoft .NET Framework 4.x** entries. If none are found, install the .NET Framework 4.5 by following the instructions in Section 6.2. If Microsoft .NET Framework 4.5 is listed, skip to Section 6.3.

Note: There can be more than one version of the .NET Framework on the server at the same time.

6.2 Microsoft .NET Framework 4.5 Installation

To install the .NET Framework:

1. Download .Net Framework 4.5 from the Microsoft download center at: <http://www.microsoft.com/en-us/download/details.aspx?id=30653>.
2. Double-click the downloaded file to run the **.Net Framework 4.5 setup**. The **License Terms** dialog (Figure 6-2) displays:




Figure 6-2: .NET Framework **License Terms** dialog

3. Select **I have read and accept the license terms** to accept the license agreement.
4. Click **Install**. Respond to any prompts presented as the installation proceeds. When completed, the **Installation Is Complete** dialog (Figure 6-3) displays:




Figure 6-3: .NET Framework **Installation Is Complete** dialog

5. Click **Finish** to complete the installation. If necessary, restart the server.
6. As a final step, run the Windows Updates utility to check for and install any .NET Framework updates that may be available.

It is very important to check for and install any .NET Framework updates. These updates can be critical to the stability and security of BPRM operation.

6.3 Internet Information Services 7.0 Installation




Figure 6-4: Open **Server Manager** applet

To install the Microsoft IIS:

1. From the Windows **Start** menu, select **Administrative Tools**.
2. Select **Server Manager** to display the **Server Manager** dialog.
3. Click **Roles** in the left pane. The **Roles** pane (Figure 6-5) displays.




Figure 6-5: Add Roles

4. If you already set up a web server, click **Select Roles** and skip to Step 6.
5. If you have not yet set up a web server, click **Add Roles** on the right pane. Review the **Before You Begin** dialog, and then click **Next**.
6. The **Select Server Roles** dialog (Figure 6-6) displays:




Figure 6-6: Select Server Roles dialog

7. Select **Web Server (IIS)**. The **Add Roles Wizard** (Figure 6-7) displays:



Figure 6-7: Add Roles Wizard

8. Click **Add Required Features**. The **Web Server (IIS)** dialog (Figure 6-8) displays:




Figure 6-8: Add Roles Wizard Web Server (IIS) dialog

9. Click **Next**. The **Select Role Services** dialog (Figure 6-9) displays:




Figure 6-9: Add Roles Wizard Select Role Services dialog

10. Clear any checked boxes and enable the following role services:

- **Common HTTP Features:**
 - Static Content
 - Default Document
 - Directory Browsing
 - HTTP Errors
 - HTTP Redirection
- **Application Development:**
 - ASP.NET
 - .NET Extensibility
 - ISAPI Extensions
 - ISAPI Filters
- **Health and Diagnostics (optional):**
 - HTTP Logging
 - Request Monitor
- **Security:**
 - Request Filtering
- **Performance:**
 - Static Content Compression

- Dynamic Content Compression
- **Management Tools:**
 - IIS Management Console
 - IIS 6 Metabase Compatibility

11. Click **Next** to display the **Confirm Installation Selections** dialog (Figure 6-10).




Figure 6-10: Add Roles Wizard Confirm Installation Selections dialog

12. Click **Install**. The **Installation Results** dialog (Figure 6-11) displays:




Figure 6-11: Add Roles Wizard Installation Results dialog

13. Click **Close** to complete the installation and end the process.

Note: Please review the additional steps for disabling the IIS Manager Logging feature in Appendix D.

6.4 Windows Communication Foundation Activation

To activate the Windows Communication Foundation (WCF):

1. From the Windows **Start** menu, select **Administrative Tools**.
2. Select **Server Manager** to display the **Server Manager** dialog.
3. Click **Features** in the left pane. The **Features** pane (Figure 6-12) displays.




Figure 6-12: Server Manager Features applet selected

4. Select **Add Features**. The **Add Features Wizard** (Figure 6-13) displays.




Figure 6-13: Add Features Wizard - Select Features dialog

5. Select the **.NET Framework 4.x Features**, including the WCF Activation options.

Note: The example in Figure 6-13 shows .NET Framework 3.0. You should see a different .NET Framework version on your server.

6. Click **Next**. The **Confirm Installation Selections** dialog (Figure 6-14) displays.




Figure 6-14: Add Features Wizard - Confirm Installation Selections dialog

7. Click **Install** to complete the process.
8. Click **Next** to view the **Installation Results** (Figure 6-15).




Figure 6-15: Add Features Wizard - WCF Installation results

9. Click **Close** to complete the **WCF installation**.

6.5 Adding MIME Types

To add MIME types:

1. From the Windows **Start** menu, select **Administrative Tools**.




Figure 6-16: Opening **Internet Information Services (IIS) Manager**

2. Select **Internet Information Services (IIS) Manager** to display the IIS Management Console (Figure 6-17).




Figure 6-17: IIS Management Console

3. Select the application server in the left pane.
4. Double-click **MIME Types** to display the **MIME Types** dialog (Figure 6-18).




Figure 6-18: MIME Types window

5. Click **Add** in the **Actions** pane. The **Add MIME Type** dialog (Figure 6-19) displays:




Figure 6-19: Blank Add MIME Type dialog




Figure 6-20: Add MIME Type .aspx extension

6. Type **.aspx** in the **File name extension** field.
7. Type **text/html** in the **MIME type** field.
8. Click **OK**.
9. In the **MIME Types** dialog (Figure 6-18), click **Add** in the **Actions** pane on the right of the screen.




Figure 6-21: **Add MIME Type .svc** Extension

10. Type **.svc** in the **File name extension** field.
11. Type **application/soap+msbin1** in the **MIME type** field.
12. Click **OK**.
13. Click the back arrow in the upper left corner of the IIS Management Console (Figure 6-18) to return to the **IIS Manager Start** window.

6.6 HTTP Compression Configuration

To configure HTTP compression:

1. Using **Windows Explorer**, browse to **C:\Windows\System32\inetsrv\config** as shown in Figure 6-22.

Note: This folder is typically hidden; you may need to manually type the folder path in the Windows Explorer address bar.




Figure 6-22: Location of **applicationHost.config** file

2. Open the **applicationHost.config** file with a text editor such as Notepad and find the **httpCompression** tag. Figure 6-23 shows a typical applicationHost.config file after scrolling down to the **httpCompression** tag.

Note: The statements following the tag in the file on the system might not match those in this example.

```
<httpCompression directory=
"%SystemDrive%\inetpub\temp\IIS Temporary Compressed Files">
<scheme name="gzip" dll="%Windir%\system32\inetsrv\gzip.dll" />
  <dynamicTypes>
    <add mimeType="text/*" enabled="true" />
    <add mimeType="message/*" enabled="true" />
    <add mimeType="application/x-javascript" enabled="true" />
    <add mimeType="*/*" enabled="false" />
  </dynamicTypes>
  <staticTypes>
    <add mimeType="text/*" enabled="true" />
    <add mimeType="message/*" enabled="true" />
    <add mimeType="application/javascript" enabled="true" />
    <add mimeType="*/*" enabled="false" />
  </staticTypes>
</httpCompression>
```

Figure 6-23: Section of a typical applicationHost.config file

3. If not already present in your applicationHost.config file, ensure the dynamic compression level and dynamic type statements are added to the file as shown in Figure 6-24:

```

<httpCompression directory=
  "%SystemDrive%\inetpub\temp\IIS Temporary Compressed Files">
<scheme name="gzip" dll="%Windir%\system32\inetsrv\gzip.dll"
dynamicCompressionLevel="5" />
  <dynamicTypes>
    <add mimeType="text/*" enabled="true" />
    <add mimeType="message/*" enabled="true" />
    <add mimeType="application/x-javascript" enabled="true" />
    <add mimeType="application/javascript" enabled="true" />
    <add mimeType="application/json" enabled="true" />
    <add mimeType="*/*" enabled="false" />
  </dynamicTypes>
  <staticTypes>
    <add mimeType="text/*" enabled="true" />
    <add mimeType="message/*" enabled="true" />
    <add mimeType="application/javascript" enabled="true" />
    <add mimeType="*/*" enabled="false" />
  </staticTypes>
</httpCompression>

```

Figure 6-24: Typical applicationHost.config file after changes

4. When finished editing the applicationHost.config file, save it and exit from the text editor.

6.7 Moonwalk Web Site Setup

6.7.1 Add the Application Pool

To add the Application Pool:

1. Return to the **IIS Manager** opened in Section 6.5 and browse to **Application Pools** in the tree structure below your IIS node as shown in Figure 6-25.




Figure 6-25: IIS Manager browsed to **Application Pools**

2. Right-click **Application Pools** and select **Add Application Pool**. The **Add Application Pool** dialog (Figure 6-26) displays.




Figure 6-26: Add Application Pool dialog

3. In the **Name** field, type the name of the application pool (**Moonwalk**).
4. In the **.NET Framework version:** field, select version 4.x of the .NET Framework.
5. Click **OK**.
6. Right-click the newly-created application pool in **IIS Manager** and click **Advanced Settings**. A dialog similar to Figure 6-27 displays:




Figure 6-27: Application Pool Advanced Settings

7. Change the **Idle Time-out** value to **120** minutes.
8. Change the **Identity** value to **LocalSystem**.
9. Click **OK** to save the changes and close the dialog.

6.7.2 Create a Moonwalk Folder

To aid in setting up the Moonwalk website, create a C:\inetpub\Moonwalk folder:

1. Using **Windows Explorer**, navigate to **C:\inetpub** on your Windows application server.
2. Click **Organize**, and then select **New Folder**. (Alternatively, click **New Folder** in the Windows Explorer toolbar if it is present.)
3. Type **Moonwalk**, and then press **Enter** to create the C:\inetpub\Moonwalk folder.

6.7.3 Add the New Site

To add the new website:

1. Right-click **Sites** in the **Connections** pane of the IIS Manager and select **Add Web Site**. The **Add Web Site** dialog (Figure 6-28) displays.




Figure 6-28: Add Web Site dialog

2. In the **Site name** field, type **Moonwalk**.
3. Click **Select** and select the Moonwalk application pool created in the previous steps.
4. In the **Physical Path** field, browse to the C:\inetpub\Moonwalk folder created in Section 6.7.2. Be aware that the location will be different if the folder was created on a different drive.
5. Set the port number in the **Binding** section to the range of 80 through 83 unless you have a specific reason not to do so. If you use a port other than the default Port 80, ensure that port is open on your firewall.
6. Click **OK** to save the changes and close the **Add Web Site** dialog.

6.8 Install the SSL Certificate

To install the SSL server certificate acquired in Section 5.1:

1. From the Windows **Start** menu, select **Administrative Tools**.
2. Select **Internet Information Services (IIS) Manager**.



Figure 6-29: Internet Information Services (IIS) Manager

3. Click the server name in the left panel.




Figure 6-30: Complete Certificate Request dialog

4. Double-click **Server Certificates** in the **Security** section (near the bottom of the panel).
5. In the **Actions** panel (on the right), click **Complete Certificate Request**. The **Complete Certificate Request** dialog displays.

Note: The Complete Certificate Request must be complete on the same system where the Certificate Signing Request was generated (Section 5.1.1, Step 11) to ensure the private key is correctly associated with the new certificate.

6. Click the ellipses button (...) to browse to the location where the server certificate file acquired in Section 5.1 is saved.
7. In the **Friendly name** field, type the friendly name for the certificate. This name is intended for use for management of certificate stores on the server.
8. In the **Select a certificate store for the certificate** field, verify **Personal Store** is selected.
9. Click **OK** to complete the procedure.

6.9 Configure the SSL Certificate

Note: If you configure the SSL certificate after installing the BPRM application, you must uninstall BPRM before configuring the SSL certificate. See Section 4.1 for information about uninstalling BPRM.

To configure the SSL certificate:

1. In the **IIS Manager** window, select the name of the server where the certificate was installed.
2. Under **Sites**, select the site to be secured with the SSL certificate.
3. In the **Actions** pane, click **Bindings**.
4. Click **Add**.
5. In **Add Site Binding**:
 - a. For **Type**, select **https**.
 - b. For **IP address**, select **All Unassigned**, or the IP address of the site.
 - c. For **Port**, specify a port number ranging from **440** through **443**.

Note: When installing SSL with https (port 440 through 443), first remove any previous site bindings for http (port 80 through 83). The **Site Bindings** dialog shown in will indicate whether there any http site bindings and allow their removal.

d. Select the **SSL certificate** just installed. Click **OK**.




Figure 6-31: **Edit Site Binding** dialog

6. Click **Close**.
7. Close **Internet Information Services (IIS) Manager**.

The SSL Certificate is now configured. Visit the website via an HTTPS connection, using the domain name, not the IP address, to verify the installation.

7.0 BPRM Database Server Installation and Configuration

This section outlines the steps essential for setting up and configuring an IHS RPMS database server for the BPRM application to be executed against the RPMS database. It also provides steps to set up such an environment.

7.1 Assumptions

This section assumes the following:

- Ensemble/Cache server (running one of the supported versions as described in Section 2.4.1) has already been set up.
- An RPMS database is already set up on the Ensemble/Cache server.
- The person performing the installation and configuration has the appropriate rights to mount databases, create a namespace, and edit namespace settings for the RPMS database.
- The BMW CACHE.DAT file provided by OIT SQA as described in the *BMW CACHE.DAT Installation Guide* document is installed.

7.2 Importing a New BPRM XML File

A separate XML file is included with the release; follow the steps in Sections 7.2.1 through 7.2.2 to import a new BPRM XML file.

7.2.1 Disable Read Only

In order to import the **bprm0300.06.xml** file, you must set the BMW database to allow write access. If the database is set to **Read Only**:

1. Browse to the **Local Databases** window of the Ensemble Management Portal following this path:

Home > System Administration > Configuration > System Configuration > Local Databases.

2. Click **Edit** in the row corresponding to the **BMW** database.
3. In the window displayed, set the **Read Only?** field to **No**.

Once the patch is installed, you can re-enable Read Only mode by repeating these steps and setting the **Read Only?** field to **Yes**.

7.2.2 Import the BPRM XML File

To import the **bprm0300.06.xml** file:

1. From the **Ensemble/Cache System Management Portal Home** window, click **System Explorer**, and then click **Classes**. The **Classes** dialog (Figure 7-1) displays.




Figure 7-1: **Classes** dialog

2. Select the **BMW** namespace in the **LookIn:** pane on the left side of the dialog.
3. Click **Import**. The **Import Classes** dialog (Figure 7-2) displays.




Figure 7-2: **Import Classes** dialog

4. Click **Browse** and navigate to the **bprm0300.06.xml** file in the folder where it is saved as described in Section 3.0.
5. Select the **bprm0300.06.xml** file and click **Next**.
6. A listing (Figure 7-3) displays, showing the contents of the XML file.




Figure 7-3: **Import Classes** window - content listing

7. Click **Import**. After a few moments of processing, a listing of the imported classes (Figure 7-4) displays.




Figure 7-4: **Import Classes** window - Import listing

8. Scroll to the bottom of the listing to confirm the **Load finished successfully** message displays (Figure 7-5).




Figure 7-5: **Import Classes** window - Load finished successfully

At this point, the BMW database configuration is complete.

7.3 Cache User Creation

BPRM performs CRUD operations over the RPMS DB using the BMW tables that were mapped over the RPMS database.

BPRM requires a Cache user privileged to execute CRUD on the RPMS database. Table 7-1 shows the privileges needed:

Table 7-1: User Permissions Needed

Item	Permissions Needed
SQL Tables	Update/Read/Delete privilege on all tables of the BMW package in the RPMS database
SQL Views	Read permission all views of the BMW package in the RPMS database
SQL Procedures	Execute permission on all procedures of the BMW package in the RPMS database

7.3.1 Create the Moonwalk User

To create a new Moonwalk user:

1. Navigate to the **Users** window of the Ensemble System Management Portal following this path:
Home > System Administration > Security > Users.
2. Click **Create New User** to display the **Edit User** window (Figure 7-6).

The screenshot shows the 'Edit User' window in the Ensemble System Management Portal. The window title is 'Edit User' and it includes a navigation breadcrumb: 'System > Security Management > Users > Edit User'. The server information is displayed as 'Server: law-pc', 'User: sa', 'Namespace: %SYS', 'Switch', 'Licensed to: LLC', and 'Instance: CACHE'. The main content area is titled 'Use the form below to create a new user definition:' and contains several tabs: 'General', 'Roles', 'SQL Privileges', 'SQL Tables', 'SQL Views', and 'SQL Procedures'. The 'General' tab is active, showing a form with the following fields: 'Name' (MOONWALK_USER), 'Copy from' (an existing name here), 'Full Name', 'Comment', 'Password' (masked with dots), 'Confirm Password' (masked with dots), 'Change password on next login' (checkbox), 'User Enabled' (checkbox, checked), 'Expiration Date' (calendar icon, format yyyy-mm-dd), 'Startup Namespace' (dropdown), and 'Startup Tag/Routine'. There is also a 'Two-factor Authentication' section with 'Mobile phone service provider' (dropdown) and 'Mobile phone number' (text input). At the bottom right, there are 'Save' and 'Close' buttons. A small note at the bottom left states '* Indicates a required field'.

Figure 7-6: Edit User window

3. Type **MOONWALK_USER** in the **Name** field.
4. Type a password that complies with your site-specific password rules in the **Password** and **Password Confirmation** fields.
5. Click **Save** to save the new user.
6. Click **Close** to exit the **Edit User** window.

7.3.2 Assign User Roles

To assign user roles for the required tables:

1. Navigate to the **Users** window (Figure 7-7) in the **Ensemble System Management Portal** following this path:

Home > System Administration > Security > Users.

The screenshot shows the 'Users' window in the Ensemble System Management Portal. The breadcrumb navigation is 'System > Security Management > Users'. The page includes a 'Create New User' button and a table of user definitions. The table has columns for User, Full Name, Enabled, Namespace, Routine, and Type. The MOONWALK_USER user is highlighted, and its 'Edit' button is circled in red.

User	Full Name	Enabled	Namespace	Routine	Type			
_PUBLIC	(Internal use - not for login)	No			Cache password user	Edit	-	Profile
_SYSTEM	SQL System Manager	Yes			Cache password user	Edit	-	Profile
Admin	System Administrator	Yes			Cache password user	Edit	Delete	Profile
CSPSystem	CSP Gateway user	Yes			Cache password user	Edit	Delete	Profile
Jawad	User who installed system	Yes			Cache password user	Edit	Delete	Profile
MOONWALK_USER		Yes			Cache password user	Edit	Delete	Profile
sa		Yes			Cache password user	Edit	Delete	Profile
SuperUser	System Super user	Yes			Cache password user	Edit	Delete	Profile
UnknownUser	Unauthenticated user	Yes			Cache password user	Edit	-	Profile

Figure 7-7: **Users** window

2. Click **Edit** in the row corresponding to the new MOONWALK_USER user created in Section 7.3.1. The **Edit User** window (Figure 7-8) displays.




Figure 7-8: Roles tab in Edit User window – before changes

3. Click the **Roles** tab.
4. Select **%ALL** from the **Available** column and move it to the **Selected** column by clicking the right arrow.
5. Click **Assign** to assign the **%ALL** role to the MOONWALK_USER account. When done, the **Edit User** window will look similar to that shown in Figure 7-9.




Figure 7-9: Roles tab in Edit User window – after changes

7.3.3 Verify XML Import and Installation

To verify the XML file has been imported and is readily available:

1. Browse to the **Schemas** window (Figure 7-10) of the Ensemble System Management Portal following this path:

Home > System Explorer > SQL > Browse SQL Schemas.




Figure 7-10: Schemas window with Procedures

2. Select the site-specific namespace (**EBCI** in the example) from the column on the left.
3. Click **Procedures** in the **BMW_BSF_SP** row. The **Stored Procedures** window (Figure 7-11) displays.




Figure 7-11: Stored Procedures window

4. Type **core** in the **Filter** field.

5. Click **Run** on the row containing the name **Core_AuthenticateUserQ**.
6. If the Ensemble version is compatible with the newly-installed BMW Cache classes, the **Run Query** window (Figure 7-12) displays.

Menu Home | About | Help | Logout System > SQL > Schemas > Stored Procedures > Run Query
Server: TrainingDB Namespace: EBCI This is a Test System
User: pieran Licensed to: Property of the Indian Health Service Instance: ENSEMBLE12

Run Query

Details
SQL query from stored procedure Core_AuthenticateUserQ in namespace EBCI
[BMW.BSF.SP.CoreAuthenticateUser : AuthenticateUserQ](#)

Enter values for the query parameters:

AccessCode	<input type="text"/>	xDBC Type VARCHAR
VerifyCode	<input type="text"/>	VARCHAR
FacilityIen	<input type="text"/>	VARCHAR

Run Query

Figure 7-12: **Run Query** window

7. If an error message is displayed, the Ensemble version running is not compatible with the newly-installed BMW Cache classes.

8.0 Application Deployment to the Web Server

With the application and database server installations complete, this section describes the steps for installing the BPRM application itself.

Note: If installing an update or patch to an existing BPRM installation, first uninstall the previous version before continuing. See Section 4.0 for instructions.

8.1 Deploy the BPRM Application

To deploy the BPRM application:

1. Log onto the application server and browse to the location where the BPRM Application Installer file (**bprm0300.06.msi**) is stored.
2. Double-click the **bprm0300.06.msi** file to run the BPRM application installer.

Note: If an error message displays indicating that you do not have sufficient privileges to run the installer, refer to Appendix A for instructions on running the installer from the Administrator command prompt.

3. Once the installer is started, the **BPRM setup wizard** (Figure 8-1) displays.




Figure 8-1: **BPRM Setup Wizard** dialog

4. Click **Next**. The **Select Installation Address** dialog displays.

5. Select **Moonwalk** from the **Site** list.
6. Type the directory name in the **Virtual directory** field, if necessary.
7. Select **Moonwalk** from the **Application Pool** list. Figure 8-2 shows the results:




Figure 8-2: **Select Installation Location** dialog after selection

8. Click **Next**. The **Confirm Installation** (Figure 8-3) dialog displays.




Figure 8-3: **Confirm Installation** dialog

9. Click **Next**. The **Installing BPRM** dialog (Figure 8-4) displays and the installation progress is shown.




Figure 8-4: **Installing BPRM** dialog

10. After a few moments of processing, the **Database Configuration** dialog (Figure 8-5) displays.




Figure 8-5: **Database Configuration** dialog

11. The BPRM suite relies on specific information about each RPMS database to which it is connected. Click **Add** in the **Database Configuration** dialog to display the **Configuration** dialog (Figure 8-6) and add this information for each database associated with this installation.

Figure 8-6: **Configuration** dialog

The **Database Configuration** dialog contains the following fields:

- **Database IP:** Use this field to enter the IP address of your RPMS database. Note that this is the internal IP address, not an external address.
- **Namespace:** Use this field to enter the namespace of your RPMS database.
- **DB User Name:** This field is automatically populated with the MOONWALK_USER user name.
- **Password:** Use this field to enter the password you set for the MOONWALK_USER account in section 7.3.1.
- **Port:** Use this field to enter the Cache Superserver port used by your RPMS database. By default, this is port 1972, although it will be different on your system if you have changed this Cache setting.

You can check your Superserver port number from within the Ensemble Management Portal using this path:

Home > Configuration > Memory and Startup

The Superserver port number displays at the bottom of the page displayed.

- **Short Name:** This field is automatically populated with your institution's short name if it exists in your INSTITUTION file. If it does not exist, type a short name of your choice by which you can identify this institution in the future.
- **Institutions:** Use this list box to choose the institutions associated with your RPMS database. When the **Default** check box is enabled, this list is limited to only the institutions set as your default per your INSTITUTION file. When the check box is cleared, the list will show all available institutions.

12. When the **Configuration** dialog displays, enter the **Database IP, NamespaceDB User Name, Password, and Port**, then click **Verify Connection**. Once the **Institutions** list is loaded, select your institution from the list and provide a **Short Name** (if not already present).
13. Once the fields are populated, click **Save** to add the information to the BPRM database configuration file. If more than one database is associated with this installation of BPRM, re-populate the form fields with the appropriate information and click **Save** again. Repeat this process for each database.
14. When done, click **Continue** to continue the application installation.
15. A **Moonwalk Setup Status Page** (Figure 8-7) will display to perform a setup check. The checks listed should display as complete.




Figure 8-7: Moonwalk Setup Status Page

16. When the installation is complete, click **Next**. The **Installation Complete** dialog Figure 8-8 displays.




Figure 8-8: **Installation Complete** dialog

17. Click **Close** to exit the dialog.

8.2 Adding a Database after the Installation

In some cases, and at some sites, it may be necessary or desirable to associate one or more additional databases to the BPRM application suite. To add a database after BPRM has been installed:

1. Log onto the application server where BPRM resides.
2. Browse to the location where the BPRM Application Installer file (**bprm0300.06.msi**) is stored.
3. Double-click the **bprm0300.06.msi** file to run the BPRM application installer. The **BPRM setup wizard** (Figure 8-9) displays in repair mode.




Figure 8-9: **BPRM Setup Wizard** dialog – repair mode

4. Select **Repair**, and then click **Finish**. The **Installing BPRM** dialog (Figure 8-10) displays.




Figure 8-10: **Installing BPRM** dialog

5. Click **Next** once the processing is complete. The **Database Configuration** dialog (Figure 8-11) displays.




Figure 8-11: Database Configuration dialog

6. In the **Database Configuration** dialog, click **Load Existing Configuration**. The **Configuration File Selection** dialog (Figure 8-12) displays.




Figure 8-12: Configuration File Selection dialog

7. Select **Facilities** and click **Open**. The **Database Configuration** dialog displays again, with the existing configuration listed, similar to that shown in Figure 8-13.




Figure 8-13: **Database Configuration** dialog - Existing configurations listed

8. Click **Add** in the **Database Configuration** dialog to display the **Configuration** dialog.
9. When the **Configuration** dialog displays, enter the **Database IP**, **NamespaceDB** **User Name**, **Password**, and **Port**, then click **Verify Connection**. Once the **Institutions** list is loaded, select your institution from the list and provide a **Short Name** (if not already present).
10. Once the fields are populated, click **Save** to add the information to the BPRM database configuration file. Repeat this process for each database.
11. When done, click **Continue** to continue the application installation.
12. When the installation is complete, the **Installation Complete** dialog Figure 8-14 displays.




Figure 8-14: Installation Complete dialog

13. Click **Close** to exit the dialog.

8.3 Menu and Security Keys

There are no package-specific security keys associated with BPRM. The BPRM package operates on existing RPMS security keys.

BPRM security is built upon the RPMS Menus and Security keys. Table 8-1 defines the relationship between BPRM Roles and the RPMS Menu and Security keys.

Note: If a user has AKMOCORE or AKMOEVE as their primary menu option, either of these menu options will override any of the Secondary Menu options shown in Table 8-1. They will, however, need the appropriate Security Keys as shown in the table.

Table 8-1: Security Keys

Role	Secondary Menu Option	Security Keys (Must include all)
ADT Clerk	BDGMENU	DGZADT DGZNUR DGZMENU
ADT Coder	BDGMENU	DGZPCC DGZMENU

Role	Secondary Menu Option	Security Keys (Must include all)
ADT Supervisor	BDGMENU	DGZADT DGZICE DGZNUR DGZSUP DGZSYS DGZMENU
ADT Non-Clinical	BDGMENU	DGZNOCLN DGZMENU
Admin		XUPROG XUPROGMODE
CQM Clerk	APCLMENU	APCLZMENU
CQM Supervisor	APCLMENU	APCLZMENU XUPROG XUPROGMODE
Flag Manager		DGPF MANAGER
Flag Assignment		DGPF ASSIGNMENT
Flag Access		DGPF PRF ACCESS
PHR Operate	AGPAT – or – AGVIEWONLY	AGZPHROPT
Registration Clerk	AGPAT – or – AGMENU	AGZMENU
Registration Supervisor	AGMENU	AGZMENU AGZMGR AGZHOME AGZREPORTS AGZDELHRN
Registration View Only	AGPAT – or – AGVIEWONLY	AGZVIEWONLY
Scheduling Clerk	BSDMENU	SDZMENU
Scheduling Supervisor	BSDMENU – or – BSD MENU SUPERVISOR	SDZMENU SDZSUP
SSN Viewer	AGSSNMENU	AGZVIEWSSN

In cases where there is more than one Secondary Menu Option listed in Table 8-1, only one is necessary per user. Conversely, where there is more than one Security Key listed for a specific role, all of the keys shown must be included. For example, a Scheduling Supervisor needs either the BSDMENU or BSD MENU SUPERVISOR added as a Secondary Menu Option but needs both the SDZMENU and SDZSUM Security Keys.

8.4 Open the BPRM Application

After the installation and configuration steps have been done, to open BPRM:

1. Open Internet Explorer.
2. In the Address bar, enter the IP address of your Windows application server and the port number using this form, where *domain_name* represents the IP address of the application server and *k* represents the port number you assigned in Section 6.9:

For sites using SSL:

https://domain_name:kkk

For sites not using SSL:

http:// ip_address:kk

3. If Microsoft Silverlight is not already installed on the computer, a message will be displayed offering to download and install it. Follow the prompts to install Silverlight on the computer.
4. Once Silverlight is installed, the BPRM **Log In** screen (Figure 8-15) displays.

Figure 8-15: BPRM **Log In** screen

5. Type your RPMS Access Code (user name) in the **Access Code** field.
6. Type your RPMS Verify Code (password) in the **Verify Code** field.
7. Select your RPMS database from the **Database** list box.

Note: Users must have an RPMS division assigned to them before they can log into the RPMS database selected in this step.

8. Click **Login**. A screen similar to that shown in Figure 8-16 will display, although different modules may display at the bottom of the screen.




Figure 8-16: BPRM Opening Screen

Note: If you specified a port other than the default in Section 6.7.3 and the opening screen is not displayed, verify that the port you specified is open on the BPRM web server.

Refer to the separate BPRM User Manuals for additional information about using the modules that make up the application suite.

Appendix A: Run the Application Installer from the Command Prompt

In cases where you do not have sufficient privileges to install the BPRM application, an error message similar to the one shown in Figure A-1 displays.




Figure A-1: Insufficient privileges error message

If this happens, it will be necessary to install the application as an Administrator:

1. Navigate to **C:\Windows\system32** on your application server.
2. Locate the cmd.exe file, right-click, and select **Run as Administrator**.
3. In the Command Prompt window displayed, type this command to change to the disk and directory where the BPRM application installer file is located. In this example, the file is located on drive **D:** in the **EnsembleDatabases\bprm** folder. On your system, this location will likely be different.

```
C:\Windows\system32>D:
D:\>
D:\>cd EnsembleDatabases\bprm
D:\EnsembleDatabases\bprm>
```

4. At the resulting prompt, type the name of the installation file (**bprm0300.06.msi** in this example) and press Enter:

```
D:\EnsembleDatabases\bprm>bprm0300.06.msi
```

This will launch the **BPRM setup Wizard** and at that point you can follow the steps described in Section 8.1.

Appendix B: Running Multiple Instances of BPRM

For testing purposes, it may be desirable to run multiple instances of BPRM. To set up multiple instances of BPRM:

1. Create a new application pool as described in Section 6.7.1, using a unique name for your test site (i.e., BetaMoonwalk or TestMoonwalk).
2. Create a new folder (also with a unique name for your test site) as described in Section 6.7.2.
3. Add a new website as described in Section 6.7.3, using the newly created application pool and folder. Also change the port number to avoid conflict with the original Moonwalk website.
4. Deploy the new instance of the BPRM application by following the steps shown in Section 8.1, but select the test website and application pool during the installation process.

Appendix C: Application Server Specification Example

Table C-1 shows the specifications for a typical application server capable of running the BPRM application suite. These specifications only represent an example and are not to be considered a stringent specification.

This example is from the Dell website. At the time of initial publication of this manual, the total cost for this application server (including Windows Server 2008 software) was approximately \$3,800.00.

Table C-1: Typical Application Server Specification Example

Catalog Number/Description	Product Code	Qty	SKU	ID
PowerEdge M520: PowerEdge M520 Blade Server	M520G	1	[225-3012]	1
Operating System: Windows Server 2008 R2 SP1, Standard Edition, x64, Includes 5 CALs	WS8SE5C	1	[421-5433]	11
OS Media Kits: No Operating System Media Kit	NOSDOC	1	[420-1908]	26
Onboard NIC Type (Fabric A): On-Board Broadcom 5720 Quad Port 1GBE	OBNIC	1	[331-7322]	12
Shipping: Shipping Material, Individual Blade, PE M520	SHIPGRP	1	[331-7322]	1500
Chassis Configuration: Serial-Attach SCSI Backplane	SAS	1	[331-4358]	1530
Cooling: Fresh Air Cooling	FRESHA	1	[331-7256]	1531
Processor: Intel® Xeon® E5-2407 2.20GHz, 10M Cache, 6.4GT/s QPI, No Turbo, 4C, 80W, Max Mem 1066MHz	E52407	1	[319-0019] [331-7255]	1550
Additional Processor: Intel® Xeon® E5-2407 2.20GHz, 10M Cache, 6.4GT/s QPI, No Turbo, 4C, 80W	2E52407	1	[319-0028] [319-0084] [331-7255]	1551
Memory DIMM Type and Speed: 1333 MHz RDIMMs	1333RD	1	[331-4422]	1561

Catalog Number/Description	Product Code	Qty	SKU	ID
Memory Configuration Type: Performance Optimized	PEOPT	1	[331-4428]	1562
Memory Capacity: 4GB RDIMM, 1333 MT/s, Low Volt, Single Rank, x4 Data Width	4R3LSR	2	[317-9649]	1560
RAID Configuration: Hardware RAID 1	MSSR1	1	[331-7249]	1540
RAID Controller: H310 Controller	H310	1	[331-4365]	1541
Hard Drives: 146GB 15K RPM SAS 6Gbps 2.5in Hot-plug Hard Drive	146A15H	1	[342-3493]	1570
Embedded Systems Management: iDRAC7 Enterprise for Blades with Vflash, 8GB SD card	IDRENV8	1	[342-1413] [421-5357]	1515
System Documentation: No Systems Documentation, No OpenManage DVD Kit	NODOCS	1	[310-5171]	1590
Hardware Support Services: 3Yr Basic Hardware Warranty Repair: 5x10 HW-Only, 5x10 NBD Onsite	U3OS	1	[939-7067] [939-7187] [939-7307] [994-4019] [995-9091] [995-9911]	29
Installation Services: No Installation	NOINSTL	1	[900-9997]	32
Proactive Maintenance: Maintenance Declined	NOMAINT	1	[926-2979]	33

Appendix D: Disable Logging in IIS Manager

The Internet Information Services (IIS) manager is set up by default with a Logging feature which allows it to capture certain types of requests to log files in the IIS installation folder. We recommend disabling this logging feature for the Moonwalk websites as it may result in storage issues if the log file is not maintained or monitored.

The following steps show how to disable the Logging feature for each Moonwalk website setup at your site. This information can also be found on the Microsoft website at:

<https://technet.microsoft.com/en-us/library/cc754631%28v=ws.10%29.aspx>.

1. From the Windows **Start** menu, select **Administrative Tools**.




Figure D-1: Opening **Internet Information Services (IIS) Manager**

2. Select **Internet Information Services (IIS) Manager** to display the IIS Management Console.




Figure D-2: IIS Management Console

3. Select the **Moonwalk** website in the left pane.
4. Double-click **Logging** to display the **Logging** dialog.




Figure D-3: Logging window

5. Click **Disable** in the **Actions** pane.




Figure D-4: Disabled Logging window

Appendix E: Run Multiple BPRM Web Applications on a Single Server

For CQM purposes, it may be necessary to set up multiple instances of the same BPRM if multiple databases are hosted under one website. To set up multiple instances of BPRM:

1. Create a new application pool as described in Section 6.7.1, using a unique name for your test site (i.e., Moonwalksite1 or Moonwalksite2).
2. Create a new folder (also with a unique name for your site) as described in Section 6.7.2.
3. Add a new website as described in Section 6.7.3, using the newly created application pool and folder. Also change the port number in order to avoid conflict with the original Moonwalk website.
4. Copy the contents from the original Moonwalk folder to the new folder created in step 2.
5. In the new moonwalk folder, go to the **Config** folder and open the **facilities.xml** file using notepad or an xml editor.
6. Remove the <Server Id> section for the database using the original install. If needed, manually add in the <Server Id> information for the database that will be using the new install. Save the file once changes are completed.
7. In the new moonwalk folder, open the **web.config** file using notepad or an xml editor to edit the file.
8. Go to the <appSettings> section and edit the "**CqmTransactionDatabase**" tag to append the site's institution IEN to the value="CqmTransaction" using the underscore character as shown in Figure E-1. Save the file once the changes are completed.

```
<appSettings>
  <add key="aspnet:UseTaskFriendlySynchronizationContext" value="true" />
  <add key="webpages:Version" value="3.0.0.0" />
  <add key="webpages:Enabled" value="false" />
  <add key="PreserveLoginUrl" value="true" />
  <add key="ClientValidationEnabled" value="true" />
  <add key="UnobtrusiveJavaScriptEnabled" value="true" />
  <add key="nhibernate-logger"
value="Moonwalk.Infrastructure.Common.Logging.CommonLoggingLoggerFactory,
Moonwalk.Server.Infrastructure" />
  <add key="LOGENTRIES_TOKEN" value="93e6e115-fd81-49f6-89af-
fd6b97e91209" />
  <add key="LOGENTRIES_ACCOUNT_KEY" value="23f637e6-43f7-4322-a532-
34886184e7d9" />
  <!--<add key="LOGENTRIES_LOCATION" value="" />-->
  <add key="CqmStoreUrl" value="http://127.0.0.1:27019" />
```

```
<add key="CqmReferenceDatabase" value="CqmReference" />
<add key="CqmTransactionDatabase" value="CqmTransaction_SiteIen" />
<add key="CqmUser" value="1" />
<add key="assignedAuthor" value="IHS eCQM" />
</appSettings>
```

Figure E-1: Web.config file after changes

9. The final step is to start the new application pool and new website.

Acronym List

Acronym	Term Meaning
CRUD	Create, Read, Update, and Delete
IHS	Indian Health Service
IIS	Internet Information Service
PHR	Personal Health Record
RPMS	Resource and Patient Management System
SSL	Secure Sockets Layer
WCF	Windows Communication Foundation

Contact Information

If you have any questions or comments regarding this distribution, please contact the OIT Help Desk (IHS).

Phone: (888) 830-7280 (toll free)

Web: <http://www.ihs.gov/helpdesk/>

Email: support@ihs.gov